

Kit Contents		
Description	**Part No**	**Pcs**
Shock absorber	HA 901	1
Sticker set	10207-01	1
Sticker Memo notes	01180-01	1
Owner´s manual	07241-02	1

Note!

Please note that there can be small differences between your product and the images in these instructions.

Note!

Please note that during storage and transport, especially at high ambient temperature, some of the oil and grease used for assembly may leak and stain the packaging. This will not cause damage to the product, wipe off the excessive oil or grease with a cloth.

Note!

Before you install this product, check the kit contents. If anything is missing, please contact an Öhlins dealer.

⚠ Warning!

Before you install this product, read the Öhlins Owner's manual. This product is an important part of the vehicle and the vehicle stability.

Shock absorber for Husqvarna Norden 901

HA 901

Mounting Instructions

ÖHLINS
ADVANCED SUSPENSION TECHNOLOGY

MOUNTING INSTRUCTIONS

⚠ Warning!

We strongly recommend to let an Öhlins dealer install this product.

⚠ Warning!

If you work with a lifted vehicle, make sure that it is safely supported to prevent it from tipping over.

Note!

When you work with this product, see the vehicle service manual for vehicle specific procedures and important data.

Note!

Before you install this product clean the vehicle.

1

Put bike on a stand so that the rear wheel barely touch the ground.

2


Refer to the vehicle manual to install the Öhlins shock absorber.

MOUNTING INSTRUCTIONS

ADJUSTMENTS

⚠ Warning!

Before you ride/drive, always make sure that the setup is according to the recommended setup data. Read about adjustments and setting up in the Öhlins Owner's Manual before you make any adjustments. Contact an Öhlins dealer if you have any questions about setting up.



SETUP DATA

Length	371.5	mm
Stroke	78	mm
Spring (part.no.)	01099-31	
Spring preload	13 +8/-2	mm
Spring rate	95	N/mm
Spring free length	220	mm
Touring		
Compression	16	Clicks
Rebound	8	Clicks
Country road (Factory setting)		
Compression	14	Clicks
Rebound	6	Clicks
Off road		
Compression	12	Clicks
Rebound	6	Clicks

Recommended Ride height		
R1-R3	75 ± 5	mm

Öhlins products are subject to continuous improvement and development, therefore, although these instructions include the most up-to-date information available at the time of printing, minor updates may occur.

To find the latest information contact an Öhlins distributor. Please contact Öhlins if you have any questions regarding the contents in this document.

Part no. MI_HA901_0
Issued 2025-06-09

© Öhlins Racing AB. All rights reserved. Any reprinting or unauthorized use without the written permission of Öhlins Racing AB is prohibited.

Öhlins Racing AB
Box 722
S-194 27 Upplands Väsby, Sweden
Phone +46 8 590 025 00
fax +46 8 590 025 80

ÖHLINS
ADVANCED SUSPENSION TECHNOLOGY

www.ohlins.com